

AIE100-903-FL NEW

Fanless Edge AI System with NVIDIA® Jetson Nano™ SoM, 1 HDMI, 1 GbE LAN, 1 GbE PoE and 2 USB

Features

- NVIDIA® Jetson Nano™ with Maxwell™ GPU architecture with 128 NVIDIA CUDA® cores
- High AI computing performance for GPU-accelerated processing
- Ideal for edge AI smart city applications
- Optional IP42 cover kit for semi-outdoor applications
- Supports one 15W GbE PoE for camera
- Wide operating temperature from -30°C to +60°C
- JetPack supported

NVIDIA Nano available through to 2025*
The official end of life notice will be sent for at least 8 months before the last shipment.




Specifications

Standard Color	Silver
Construction	Aluminum extrusion and heavy-duty steel, IP40 (without IP42 cover kit)
CPU Board	NVIDIA® Jetson Nano™
CPU	Quad-core ARM® Cortex®-A57 MPCore processor
GPU	NVIDIA Maxwell™ GPU architecture with 128 NVIDIA CUDA® cores
System Memory	1 x 4GB 64-bit LPDDR4 onboard
Carried Board	SBC87903
System I/O Outlet	1 x HDMI 2.0 with 4K2K supported 1 x 10/100/1000 Mbps Ethernet (Via Jetson™ Nano) 1 x 10/100/1000 Mbps PoE (Intel® i210-IT ;max. up to 15W) 1 x USB 3.0, 1 x USB 2.0 1 x Micro USB for image flash 1 x Recovery switch 1 x Reset button 1 x Power button 1 x 12 VDC power input connector 2 x SMA-type antenna connector
Watchdog Timer	Built-in Nano
Storage	Onboard 16GB eMMC (via Jetson™ Nano) 1 x M.2 Key M 2280 with PCIe x4 NVMe SSD slot 1 x Micro SD slot *The bootable device supported by eMMC only
Expansion Interface	1 x Full-size PCI Express Mini Card slot (USB + PCI Express signal) 1 x SIM slot
System Indicator	1 x Green LED for system power-on 1 x Yellow LED for M.2 storage
Power Supply	12 VDC screw type
Operating Temperature	-30°C to +60°C (-22°F to +140°F)
Humidity	10% - 95%, non-condensing
Vibration Endurance	3 Grms with M.2 (5 to 500Hz, X, Y, Z directions)
Dimensions	147.4 mm (5.8") (W) x 129.8 mm (5.11") (D) x 34.6 mm (1.36") (H)
Weight (net/gross)	1 kg (2.20lb)/1.6 kg (3.52lb)
Certifications	CE, FCC Class A
OS Support	Linux Ubuntu 18.04

Packing List

- 1 x Screw pack
- 4 x Foot pad



Power Protection

AC to DC Adapter

- OVP (over voltage protection)
- OCV (over current protection)
- UVP (under voltage protection)
- SCP (short circuit protection)

Ordering Information

Standard

AIE100-903-FL	Fanless edge AI system with NVIDIA® Jetson Nano™ SoM, 1 HDMI, 1 GbE LAN, 1 GbE PoE and 2 USB
---------------	--

Optional

M.2 NVMe SSD	Wall mount kit DIN-rail kit VESA mount kit 128GB or above LTE module Wi-Fi module
50966124050E	12V/60W adapter Power cord IP42 cover kit

* Specifications and certifications may vary based on different requirements.

Dimensions

