
Datasheet

Advantech

AIMB-232


-

The information contained in this document has been carefully researched and is, to the best of our knowledge, accurate. However, we assume no liability for any product failures or damages, immediate or consequential, resulting from the use of the information provided herein. Our products are not intended for use in systems in which failures of product could result in personal injury. All trademarks mentioned herein are property of their respective owners. All specifications are subject to change without notice.

AIMB-232

Intel® Core™ i7/i5/i3/Celeron BGA 1356 Mini-ITX with DP++/HDMI/LVDS(eDP), 2 COM, Dual LAN, miniPCIe, DDR4, DC Input

NEW



Features

- Supports Intel® Core™ core i7-6600u /core i5-6300u /core i3-6100u/celeron 3955u/Celeron 3965u, 15W TDP, BGA 1356,14nm Processor
- Two 260-pin SO-DIMM up to 32GB DDR4 2133 MHz SDRAM
- Multiple display I/O supports versatile Tri display functions for HDMI, DP, LVDS/eDP
- Support 2 F/S miniPCIe
- Support 12V DC Input and low profile height
- Supports 6 USB 3.0, 2 USB 2.0, TPM 1.2 / 2.0 (optional)


Software APIs:

Utilities:

Specifications

		i7-6600u	i5-6300u	i3-6100u	Celeron 3955u	Celeron 3965u
Processor System	CPU	i7-6600u	i5-6300u	i3-6100u	Celeron 3955u	Celeron 3965u
	Core Number	2	2	2	2	2
	Max Speed	2.6G	2.4G	2.3G	2G	2.2G
	L3 Cache	4M	3M	3M	2M	2M
	TDP	15W	15W	15W	15W	15W
	Chipset	Integrated PCH				
BIOS		AMI uEFI 16 Mbit				
		1 F/S miniPCIe slot support mSATA (celeron sku can't support); 1 F/S miniPCIe slot with SIM card holder				
Expansion Slot	Mini-PCIe	1 F/S miniPCIe slot support mSATA (celeron sku can't support); 1 F/S miniPCIe slot with SIM card holder				
	Technology	Dual Channel DDR4 2133 MHz SDRAM				
	Max. Capacity	16GB/8GB per SO-DIMM				
Memory	Socket	2 x 260 PIN DDR4 SO-DIMM (Non-ECC)				
	Controller	Support DirectX 11.2, OpenGL 5.0, OpenCL 2.1				
	LVDS	Supports dual channel 48-bit up to 1920 x 1200				
Graphics	HDMI	Yes, supports max. resolution 4096 x 2160 @ 60 Hz				
	DP++	Yes, supports max. resolution 4096 x 2304 @ 60 Hz				
	Dual Display	DP + HDMI, DP + LVDS (or eDP), HDMI + LVDS (or eDP)				
	Tri Display	HDMI + DP + LVDS (or eDP)				
Ethernet	Interface	10/100/1000 Mbps				
	Controller	LAN1: Intel Clarkville I219LM GbE PHY LAN2: Intel Springville I211 GbE (co-lay intel I210IT)				
	Connector	RJ-45 x 2				
SATA	Max Data Transfer Rate	600 MB/s (SATA 3.0)				
	Channel	2 (SATA III)				
Rear I/O	HDMI	1 (HDMI 1.2/1.4/2.0)				
	DP++	1				
	Ethernet	2				
	USB	CORE i: 4 (USB3.0), CELERON: 2 (USB2.0), 2 (USB3.0)				
	Audio	2 (Mic-in, Line-out)				
	DC Jack	1, DC 12V Jack				
Internal Connector	USB	2 (USB 2.0), 2 (USB 3.0)				
	LVDS/inverter	1				
	eDP	1, by BOM optional				
	Serial	2 (support RS-232 and supports 5V/12V by jumper selecting)				
	IDE	-				
	SATA	2 (SATA III)				
	SATA Power	2				
	PS/2 K/B & M/S	1				
	Mini-PCIe	2 (F/S)				
	IrDA	-				
	CPU/System/Chassis Fan Connector	1 CPU fan with 4pin header 2 System fan with 4pin header				
	Power Connector	4pin ATX, DC 12V				
	GPIO	8-bit				
Watchdog Timer	Output	System reset				
	Interval	Programmable 1 ~ 255 sec/min				
Power Requirements	Input power	12V DC Input				
	Power Consumption (Max, test in HCT)	TBD				
Environment	Temperature	Operating 0 ~ 60° C (32 ~ 140° F) with 0.7m/s air flow, depends on CPU speed and cooler solution			Non-Operating -20 ~ 70° C (-4 ~ 158° F) with 0.7m/s air flow	
	Dimensions	170 mm x 170 mm (6.69" x 6.69")				

Block Diagram



Ordering Information

Order Number	CPU	Display	GbE	TPM	Storage	USB	PCIe / PCI	Operating Temp.
AIMB-232G2-U7A1E	i7-6600u					6 x USB 3.0, 2 x USB 2.0		0 ~ 60° C
AIMB-232G2-U5A1E	i5-6300u	HDMI, DP++, LVDS/eDP (optional)	2	(1)	2 x SATA III 1 x mSATA (celeron sku didn't support mSATA)	6 x USB 3.0, 2 x USB 2.0		0 ~ 60° C
AIMB-232G2-U3A1E	i3-6100u					6 x USB 3.0, 2 x USB 2.0	2 x Full-size Mini-PCIe	0 ~ 60° C
AIMB-232G2-U0A1E	Celeron 3955u					4 x USB 3.0, 4 x USB 2.0		0 ~ 60° C
AIMB-232G2-U0B1E	Celeron 3965u					4 x USB 3.0, 4 x USB 2.0		0 ~ 60° C

Packing List

Part Number	Description	Quantity
1700003194	SATA HDD cable	2
1700018785	SATA Power cable	2
1700100250	1-to-1 serial port cable kit, 25 cm/2	2
2006B23200	Startup manual	1
1960062823N011	Fanless Heat Sink	1
1960079697T000	IO port bracket	1

Optional Accessories

Part Number	Description
96PSA-A84W12V1	ADAPTER 100-240V 84W 12V 7A
96PSA-A60W12V1-1	ADAPTER 100-240V 60W 12V 5A
1702002600	Power cable 3-pin 180 cm, USA type
1702002605	Power cable 3-pin 180 cm, Europe type
1702031801	Power cable 3-pin 180 cm, UK type
1700000237	Power cable 3-pin PSE Mark 183 cm
1960061914N021	Fan Cooler

Rear I/O



AIMB-232G2-U7A1E
 AIMB-232G2-U5A1E
 AIMB-232G2-U3A1E
 AIMB-232G2-U0A1E
 AIMB-232G2-U0B1E

Embedded OS/API

OS/API	Part No.	Description
WES7	TBD	
WES8	TBD	

Our company network supports you worldwide with offices in Germany, Austria, Switzerland, Great Britain and the USA. For more information please contact:

Headquarters

Germany



FORTEC Elektronik AG

Lechwiesenstr. 9
86899 Landsberg am Lech

Phone: +49 8191 91172-0
E-Mail: sales@forteca.de
Internet: www.forteca.de

Fortec Group Members

Austria



FORTEC Elektronik AG

Office Vienna

Nuschinggasse 12
1230 Wien

Phone: +43 1 8673492-0
E-Mail: office@fortec.at
Internet: www.fortec.at

Germany



Distec GmbH

Augsburger Str. 2b
82110 Germering

Phone: +49 89 894363-0
E-Mail: info@distec.de
Internet: www.distec.de

Switzerland



ALTRAC AG

Bahnhofstraße 3
5436 Würenlos

Phone: +41 44 7446111
E-Mail: info@altrac.ch
Internet: www.altrac.ch

United Kingdom



Display Technology Ltd.

5 The Oaks Business Village
Revenge Road, Lordswood
Chatham, Kent, ME5 8LF

Phone: +44 1634 672755
E-Mail: info@displaytechnology.co.uk
Internet: www.displaytechnology.co.uk

USA



Apollo Display Technologies, Corp.

87 Raynor Avenue,
Unit 1 Ronkonkoma,
NY 11779

Phone: +1 631 5804360
E-Mail: info@apolloDisplays.com
Internet: www.apolloDisplays.com