



OUR GLOBAL
COMPETENCE
CENTRES

 APOLLO DISPLAY
TECHNOLOGIES



 DISTEC



 DISPLAY
TECHNOLOGY




Datasheet


iBASE

IB811

**3,5" Single-Board Computer with Intel® Atom™ Apollo Lake
Pentium® N4200, Celeron® N3350 und Atom™ E39xx Processor,
eDP, 1x LVDS, 1x DisplayPort, COMs, up to -40°..+85°C**




The information contained in this document has been carefully researched and is, to the best of our knowledge, accurate. However, we assume no liability for any product failures or damages, immediate or consequential, resulting from the use of the information provided herein. Our products are not intended for use in systems in which failures of product could result in personal injury. All trademarks mentioned herein are property of their respective owners. All specifications are subject to change without notice.



Features

- Onboard Intel® Atom® x7-E3950/ x5-E3940/ x5-E3930 SoC [i-Temp support]
- Onboard Intel® Pentium® N4200/ Celeron® N3350
- 2x DDR3L-1866/1600 SO-DIMM, Max. 8GB
- Supports HDMI(1.4b), DisplayPort 24 bit dual-channel LVDS
- Dual Intel® Gigabit LAN
- Watchdog timer, Digital I/O, mSATA, EuP/ErP
- 4x USB 3.0, 2x USB 2.0, 4x COM, 2x SATA III
- 1x Mini PCI-E slot (full-size), 1x M.2 (B-key)
- Wide-range operating temperature in certain models



IB811 with Heatsink


Specifications

CPU	Intel® Atom® QC x7 /E3950 (1.6GHz~2.0GHz, 2MB cache) Intel® Atom® QC x5 /E3940 (1.6GHz~1.8GHz, 2MB cache) Intel® Atom® DC x5 / E3930 (1.3GHz~1.8GHz, 2MB cache) Intel® Pentium® QC N4200 (1.1GHz~2.5GHz, 2MB cache) Intel® Celeron® DC N3350 (1.1GHz~2.4GHz, 2MB cache)
PCH	Integrated in Intel® SoC
Memory Type	2x DDR3L SO-DIMM, Max 8GB (Non-ECC)
BIOS	AMI
Watchdog Timer	256 levels
H/W Monitor	Yes
Storage Device Interface	1x mSATA
Mini Type Slots	1x Mini PCI-E (full-size), 1x M.2 (B-key, type:3042)
Graphics Controller	Intel® SoC integrated Gen9 18EUs graphics
Video Output	Supports HDMI(1.4b), DP(1.2), 24-bit dual-channel LVDS
Ethernet	IB811F-I50/I40/I30: 2x Intel® I210IT Gigabit LAN IB811F-I420/335: 2x Intel® I211AT or I210AT Gigabit LAN
I/O Chip	Fintek F81964D-I
Serial Port	1x RS232/422/485 (jumper-less selection) 3x RS232
USB 2.0	2x USB 2.0 via pin-header
USB 3.X	4x USB 3.0 on board
Serial ATA	2x SATA III
Audio	Intel® Atom® SoC built-in HD audio controller + Realtek ALC888SHD Codec w/ class-D speaker amplifier
TPM	TPM 2.0
Others	Digital I/O, +9V~ +36V DC-In, EuP/ErP
Dimensions (L x W)	102mm x 147mm (4" x 5.8")
Power Consumption	Intel® Atom® E3900 1.3GHz w/ 2x DDR3L 1600 4GB +12V: 1.2A
Operating Temperature	E3950/E3940/E3930: -40°C~85°C (-40°F~185°F) N4200/N3350: 0°C~60°C (32°F~140°F)
Storage Temperature	-40°C~90°C (-40°F~194°F)
Relative Humidity	90% (non-condensing @60°C)

Ordering Information

IB811LF-I50	Intel® Atom® x7/ E3950 (1.6GHz~2.0GHz) 3.5" SBC w/ dual GbE LAN, HDMI, DisplayPort & LVDS (24-bit LVDS dual-channel), mSATA, M.2, EuP/ErP, 9V~36V DC-in, wide temp. support
IB811LF-I40	Intel® Atom® x5/ E3940 (1.6GHz~1.8GHz) 3.5" SBC w/ dual GbE LAN, HDMI, DisplayPort & LVDS (24-bit LVDS dual-channel), mSATA, M.2, EuP/ErP, 9V~36V DC-in, wide temp. support
IB811LF-I30	Intel® Atom® x5/ E3930 (1.3~1.8GHz) 3.5" SBC w/ dual GbE LAN, HDMI, DisplayPort & LVDS (24-bit LVDS dual-channel), mSATA, M.2, EuP/ErP, 9V~36V DC-in, wide temp. support
IB811LF-420	Intel® Pentium® N4200 (1.1~2.5GHz) 3.5" SBC w/ dual GbE LAN, HDMI, DisplayPort & LVDS (24-bit LVDS dual-channel), mSATA, M.2, EuP/ErP, 9V~36V DC-in
IB811LF-335	Intel® Celeron® N3350 (1.1~2.4GHz) 3.5" SBC w/ dual GbE LAN, HDMI, DisplayPort & LVDS (24-bit LVDS dual-channel), mSATA, M.2, EuP/ErP, 9V~36V DC-in
HSIB811-B	Heatsink for IB811F-420/ 335
HSIB811-I-A	Heatsink for IB811F-I50/ I40/ I30
HSIB811-1	Heat spreader for IB811F-420/ 335
HSIB811-I-1A	Heat spreader for IB811F-I50/ I40/ I30
IB76A-2	Cable kit w/ USB, COM, Power, SATA + Power


Dimensions and Drawing



Intel® Entry Processor Ultra Low Power Reference Table


Processor Number	Intel® Pentium® Processors - 14 nm Apollo-Lake SoC Platform	Intel® Celeron® Processors - 14 nm Apollo-Lake SoC Platform	Intel® Atom™ Processors - 14nm or Apollo-Lake-I SoC Platform		
	N4200	N3350	x7-E3950	x5-E3940	x5-E3930
Base Freq (GHz)	1.1	1.1	1.6	1.6	1.3
Intel® Turbo Boost Technology 2.0 (GHz)	2.5	2.4	2.0	1.8	1.8
Last Level Cache	2M	2M	2M	2M	2M
Cores/Threads	4/4	2/2	4/4	4/4	2/2
Memory Speed (DDR3L)	1866	1600	1866	1866	1866
TDP	6W	6W	12W	9W	6.5W

IB811 with heatsink for Pentium® & Celeron® SoC



Intel® Pentium® QC N4200
Intel® Celeron® DC N3350

IB811 with heatsink for Atom™ SoC



Intel® Atom™ QC x7 / E3950
Intel® Atom™ DC x5 / E3930

IB811 – 3,5" SINGLE-BOARD COMPUTER



BOARD / TFT-DISPLAY KITS WITH CABLES AND ACCESSORIES

Display Size	15,6" (39.6cm)	21,5" (54.61cm)
Part Number	G156HAB01.0	G215HVN01.0
Manufacturer	AUO	AUO
Resolution	1920x1080	1920x1080
Brightness [cd/m2]	300	300
Backlight	LED	LED
Converter	integrated	integrated
Viewing Angle v/h	tbd.	178°/178°
Interfaces	eDP	LVDS
Dimensions mm	363x229x4.9	495.6x292.2x12.7
Touch	PCAP	

Form Factor	3,5" Single-Board Computer
Manufacturer	iBASE
Part Number	IB811F-335
Processor	Intel® Celeron® N3350
Memory	4GB DDR3L (optional up to 8GB)
SSD	64GB MLC mSATA (included)
Expansion Slot	1x miniPCIe/mSATA, 1x M.2
Display Interface	HDMI 1.4b
LVDS	24-bit Dual Channel LVDS or eDP
LAN	2x Gigabit LAN
SATA	2x SATA III
	1x RS232/422/485, 3x RS232
I/O	4x USB 3.0, 2x USB 2.0
	Digital I/O, TPM
Power	9V – 36V DC-in



Other configuration on request!

Our company network supports you worldwide with offices in Germany, Austria, Switzerland, the UK and the USA. For more information please contact:

Headquarters

Germany



FORTEC Elektronik AG

Augsburger Str. 2b
82110 Germering

Phone: +49 89 894363-0
E-Mail: sales@fortecag.de
Internet: www.fortecag.de

Fortec Group Members

Austria



FORTEC Elektronik AG

Office Vienna

Nuschingasse 12
1230 Wien

Phone: +43 1 8673492-0
E-Mail: office@fortec.at
Internet: www.fortec.at

Germany



Distec GmbH

Augsburger Str. 2b
82110 Germering

Phone: +49 89 894363-0
E-Mail: info@distec.de
Internet: www.distec.de



FORTEC Elektronik AG

Lechwiesenstraße 9
86899 Landsberg am Lech

Phone: +49 8191 91172-0
E-Mail: sales@fortecag.de
Internet: www.fortecag.de

Switzerland



ALTRAC AG

Bahnhofstraße 3
5436 Würenlos

Phone: +41 44 7446111
E-Mail: info@altrac.ch
Internet: www.altrac.ch

United Kingdom



Display Technology Ltd.

Osprey House, 1 Osprey Court
Hichingbrooke Business Park
Huntingdon, Cambridgeshire, PE29 6FN

Phone: +44 1480 411600
E-Mail: info@displaytechnology.co.uk
Internet: www.displaytechnology.co.uk

USA



Apollo Display Technologies, Corp.

87 Raynor Avenue,
Unit 1 Ronkonkoma,
NY 11779

Phone: +1 631 5804360
E-Mail: info@apolloDisplays.com
Internet: www.apolloDisplays.com